




KORAL LINE

K450E

TYPE	Front-loading dishwasher
LINE	KORAL LINE
BASKET	450x450
SIZE	530x610x760h

The KORAL line is distinguished by its wide range of models suitable for any situation. Through the electronic card, the control system provides great customisation options based on your needs, allowing you to accurately adjust any parameter and ensure optimum washing results. The tempered glass UNIKO-MID lcd-touch display is extremely reliable and ensures optimum performance. Selecting one of the 4 wash cycles available is really simple and practical messages on the display will allow preserving the dishwasher life.

The K450E model is the right compromise for those who want both glasses and dishes in right spaces. In fact, thanks to the supplied basket, you can wash 14 dishes per cycle. The drain pump optional allows you to handle the drain automatically and perform a partial replacement of clean water at each wash.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	KORAL LINE K450E
Dimensions - (mm) L - P - H	530x610x760h
n° baskets/hour - (+55°C)	Max 40
Height glass max	290mm
Ø height plate max	310mm
Rinsing and washing arms	Ø18 INOX
Tank heating element - Tank capacity	2,6kW - 20lt
Boiler heating element - Boiler capacity	2,5kW – 7,3lt
Washing pump (kW-Hp)	0,52kW / 0,7Hp
Total power input / Current	3,12kW / 16A
Standard input voltage	230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
STANDARD EQUIPMENT	
Saucer holder 12 pieces	1
Cutlery insert	1
Basket for 14 dishes dim.450x450x100mm	1
ACCESSORIES	
UniKo touch display with iCloud Wi-Fi control	✓
Booster pump kit 0,5Hp	✓
Drain pump kit 40W	✓
Reverse osmosis system	-
Inclined basket for wine glasses dim.450x450x170mm	✓
Kit 4 Stainless steel feet 50-70mm	✓

K450E

