




KORAL LINE K205ER

TYPE	Glasswasher
LINE	KORAL LINE
BASKET	350x350
SIZE	420x500x660h

The KORAL line is distinguished by its wide range of models suitable for any situation. Through the electronic card, the control system provides great customisation options based on your needs, allowing you to accurately adjust any parameter and ensure optimum washing results. The tempered glass UNIKO-MID lcd-touch display is extremely reliable and ensures optimum performance. Selecting one of the 4 wash cycles available is really simple and practical messages on the display will allow preserving the dishwasher life.

The K205E model, available with round basket or with square basket, is the most appropriate choice to wash cups, saucers and glasses in a very tight space. The drain pump optional allows you to handle the drain automatically and perform a partial replacement of clean water at each wash cycle.

The electronic control allows you to manage various parameters to give you an absolute customisation level and the continuous self-diagnosis allows you to minimise machine downtime, suggesting some operations to be verified. The self-cleaning cycle at the end of the day cleans the wash tank and empties the boiler from the hot water, preventing limestone forming inside. The standard double peristaltic electric rinse-aid and detergent dispenser ensures the best result from each wash cycle with great savings thanks to the precise dosage managed by the electronic card; whereas, the moulded washing and rinsing arms ensure great reliability and durability. The Thermo-stop function checks that washing and rinsing begin only when the desired temperature is reached. The bodywork is made entirely of AISI 304 steel and has been designed with all components in the front to allow easy technical assistance. Sturdy and reliable dishwashers to best deal with every moment of your day.

DISHWASHERS FEATURES	KORAL LINE K205ER
Dimensions - (mm) L - P - H	420x500x660h
n° baskets/hour - (+55°C)	Max 48
Height glass max	250mm
Rinsing and washing arms	Ø18 INOX
Tank heating element - Tank capacity	2,6kW – 13lt
Boiler heating element - Boiler capacity	2,5kW – 3,2lt
Washing pump (kW-Hp)	0,19kW / 0,25Hp
Total power input / Current	2,79kW / 16A
Standard input voltage	230V 50Hz
Recommended inlet water temperature	+55°C
Water hardness	7÷10 °f
Water consumption per cycle (inlet suggested pressure 2 BAR)	2,0lt
Adjustable detergent and rinse-aid dispenser	ELECTRIC
STANDARD EQUIPMENT	
Basket for glasses Ø350mm	2
Saucer holder 12 pieces	1
Cutlery insert	1
ACCESSORIES	
UniKo touch display with iCloud Wi-Fi control	✓
Booster pump kit 0,5Hp	✓
Drain pump kit 40W	✓
Reverse osmosis system	-
Kit 4 Stainless steel feet 50-70mm	✓

K205ER

