



VOLTAGGIO/VOLTAGE/VOLTAGE **400 Volt / 50 Hz / 3 Phase**

MODELLO MODEL MODÈLE	SUPERF. COTTURA BAKING SURFACE SURFACE DE CUISSON	CAMERE CHAMBERS CHAMBRES	VETRI DOORS VERRES	DIMENSIONI INTERNE CAMERE CHAMBER INTERNAL DIMENSIONS DIMENSIONS INTERIEURES CHAMBRES			DIMENSIONI ESTERNE FORNI OVENS EXTERNAL DIMENSIONS DIMENSIONS EXTERIEURES FOURNS			POT. TERMICA THERMAL POWER POT. THERMIQUE
				A	B	H	A	B	H	
	m²	n.	n.	cm			cm			
TA 3/4	9,00	3	9	186	160	18	258	274	210	70.000
TA 3/5	11,20	3	9	186	200	18	258	315	210	75.000
TA 3/6	13,40	3	9	186	240	18	258	355	210	80.000
TA 3/7	15,60	3	9	186	280	18	258	396	210	90.000
TA 3/8	17,90	3	9	186	320	18	258	436	210	95.000
TA 1/4 L	11,90	3	12	248	160	18	320	274	210	75.000
TA 1/5 L	14,90	3	12	248	200	18	320	315	210	90.000
TA 1/6 L	17,90	3	12	248	240	18	320	355	210	100.000
TA 1/7 L	20,90	3	12	248	280	18	320	396	210	110.000
TA 120/1	6,00	3	6	124	160	18	196	274	210	60.000
TA 120/2	7,50	3	6	124	200	18	196	315	210	70.000
TA 120/3	9,00	3	6	124	240	18	196	355	210	75.000
TA 12-4/4	8,00	4	8	124	160	18	196	274	230	65.000
TA 12-4/5	10,00	4	8	124	200	18	196	315	230	70.000
TA 12-4/6	11,90	4	8	124	240	18	196	355	230	75.000
TA 15-4/4	9,60	4	8	150	160	18	221	274	230	70.000
TA 15-4/5	12,00	4	8	150	200	18	221	315	230	75.000
TA 15-4/6	14,40	4	8	150	240	18	221	355	230	85.000
TA 18-4/4	11,90	4	12	186	160	18	258	274	230	80.000
TA 18-4/5	14,90	4	12	186	200	18	258	315	230	85.000
TA 18-4/6	17,90	4	12	186	240	18	258	355	230	90.000
TA 24-4/4	15,90	4	16	248	160	18	320	274	230	85.000
TA 24-4/5	19,90	4	16	248	200	18	320	315	230	95.000
TA 24-4/6	23,80	4	16	248	240	18	320	355	230	110.000
TA 82/4	5,25	4	4	82	160	18	144	274	230	65.000
TA 82/5	6,60	4	4	82	200	18	144	315	230	70.000
TA 82/6	7,90	4	4	82	240	18	144	355	230	75.000